

MICROSCOPE AND STEREO MICROSCOPE

CROSS REFERENCE TO RELATED APPLICATIONS

This invention claims priority of the German patent application 101 03 641.8 which is incorporated by reference herein.

5

FIELD OF THE INVENTION

The invention refers to a microscope and furthermore the invention refers to a stereo microscope.

BACKGROUND OF THE INVENTION

10 A microscope of the species is known, for example, from U.S. Pat. No. 5,303,082. This known stereomicroscope comprises a basic body on or in which microscope objectives (which in some cases comprise components used on a shared basis), two eyepieces, and a number of beam splitters are arranged. The beam splitters are provided in the beam paths between the microscope objectives and the eyepieces. The beam splitters serve on the one hand to reflect light from
15 illuminating light sources coaxially into the beam path in order to illuminate the specimen being observed, and on the other hand to create simultaneous observation capabilities.

Also known, from German Pat. No. 36 08 242, is a slit lamp microscope for ophthalmological applications in which a beam splitter is introduced into the beam
20 path between the microscope objective and the eyepiece in such a way that an image is reflected into the beam path going to the eyepiece. This image, which for example can be an angiography image, is overlaid on the "real" microscope image

so that the viewer can compare the microscope image to the angiography image and optionally superimpose them.

It is true of all the known microscopes of the species that the beam splitter or splitters are immovably introduced into the beam path, i.e. mounted immovably
5 on the basic body or chassis of the microscope or in a beam splitter housing.

This configuration of the known microscopes of the species has a number of disadvantages:

- 10 1. The beam splitters introduced immovably into the beam path or paths unnecessarily reduce the brightness of the microscope image when there is no need for reflection into or out of the respective beam path.
2. The arrangement of the respective beam splitters defines the direction in which any reflection into or out of the beam paths is accomplished.
- 15 3. The immovably installed beam splitters do not allow any possibility of variation, for example in terms of the ratio at which the incoming light intensity is split, the type of beam splitters used, or the like.
- 20 4. The two beam paths of the stereomicroscope of the species known from U.S. Pat. No. 5,303,082, and of other stereomicroscopes, are configured symmetrically; it is therefore not possible to reflect the microscope image out in the one beam path and reflect into the other beam path an image that is overlaid on the microscope image.

In addition, reference is explicitly made to the aforementioned existing art for explanation of any details not described here.

SUMMARY OF THE INVENTION

It is the object of the invention to develop a microscope or a stereo microscope such a way that it is left to the discretion of the user of the microscope as to whether – and if so, in which direction – he or she wishes to reflect light into
5 or out of the microscope beam path or paths.

The above object is achieved by a microscope comprising:

- a basic body which at least one microscope objective and at least one eyepiece,
- a beam path defined by the microscope objective and the eyepiece,
- 10 • at least one beam splitter being provided in the beam path between the microscope objective and the eyepiece, wherein the beam splitter reflects a portion of the light out of the beam path to the eyepiece or reflects images into the beam path going to the eyepiece,
- a carrier on which the beam splitter is mounted, and
- 15 • a recess in the basic body into which the carrier together with the beam splitter insertable and removable.

Additionally, the above object is achieved by a stereo microscope comprising:

- a basic body which at least one microscope objective and at least one binocular eyepiece,
- 20 • a first beam path and a second beam path defined by the microscope objective and the eyepiece,
- a beam splitter being provided in each the beam path between the microscope objective and the eyepiece, wherein the beam splitters reflect a portion of the light out of the beam path to the eyepiece or reflects images
- 25 into the beam path going to the eyepiece,
- a carrier on which the beam splitter is mounted, and

- a first and second recess in the basic body which releasably take up the carrier together with the beam splitter in the first and the second beam path.

5 The fundamental idea underlying the invention is not to arrange beam splitters and, in particular, splitter prisms, immovably in the beam path or paths of the microscope or the beam splitter housing, but rather to use a carrier on which the beam splitter is mounted. The beam splitter or splitter prism is thus a part separate from the actual optical assemblage of the microscope, which together with the carrier can be inserted into a receptacle or recess in the basic body or chassis of
10 the microscope, and can be removed again from the receptacle.

This configuration according to the present invention allows much greater flexibility, as compared to known microscopes, when using the microscope according to the present invention.

15 It is thus possible to use a variety of splitters as beam splitters. For example, a variety of intensity splitters, such as splitter prisms which reflect different intensity components or allow them to pass as a function of the particular microscope accessory used, i.e. whose splitting ratio can differ from a 50:50 ratio, can be utilized. It is also possible to use beam splitters that cause not intensity splitting but rather a wavelength-specific (i.e. wavelength-selective) and/or
20 polarization state-specific splitting.

Further optical components can also be mounted on the carrier.

Said optical components can be, for example, filters, for example laser protection filters when a laser is used as a treatment or processing light source; or polarizers. Compensation elements that compensate for different optical effects or optical
25 path lengths of the various beam splitters being used can also be utilized.

Since the beam splitter is, as a rule, incorporated into the calculation of the basic configuration of the optical assemblage of the microscope, it is furthermore

preferred that when no beam splitter is inserted into the beam path of the microscope, there is inserted into the respective recess an element, held on a carrier, whose optical properties correspond to those of the beam splitter with the exception of the splitting effect. In the case of a splitter prism, a plane-parallel
5 plate whose optical path length corresponds to that of the splitter prism used as the beam splitter can be used.

A very wide variety of modifications and additions are of course possible in the context of the basic idea according to the present invention.

For example, it is possible for several receptacles to be provided successively in
10 the beam path of the microscope, so that a very wide variety of microscope accessories can be used together.

In any event, it is preferred if the carrier is fitted into the receptacle in such a way that after insertion, the beam splitter is aligned relative to the beam path without further alignment.

15 The carriers can moreover comprise a coding that transmits to a microscope control unit information about the microscope accessory optically connected to the microscope beam path. When a laser is used as an accessory, for example, the control unit can be informed by means of the coding that a laser is mounted on the microscope. The control unit then ensures that the laser is triggered only when a
20 protective filter is inserted or pivoted into the beam path. The control unit can also perform an adaptation of the microscope on the basis of the coding, for example automatically pivoting into the beam path appropriate elements to compensate for the optical effects of the beam splitter being used.

A very wide variety of embodiments is also possible with regard to the
25 configuration of the carrier.

For example, the carrier can be an integral constituent of a microscope accessory, such as a simultaneous observation unit; an illumination or treatment or

10056046 012802

processing light source whose light can be reflected, in particular coaxially, into the beam path in order to illuminate or process the specimen being observed; or a device that, in the eyepiece image, overlays on the microscope image a reflected-in image, for example an angiography image and/or displays or the like.

- 5 Alternatively, the carrier can comprise on its end facing away from the beam splitter, i.e. its end not inserted into the receptacle, a coupling onto which various microscope accessories, such as the units mentioned above by way of example, can be mounted.

- 10 It is also possible in this context for the carrier to be insertable into the receptacle of the microscope rotated 180 degrees about an axis perpendicular to the beam path, so that the beam splitter can be used for reflecting in and reflecting out depending on the insertion direction. This means a great cost savings, since it is no longer necessary to procure multiple carriers, each with different beam splitters, for different accessories. In addition, a selection can be made as desired between
15 left and right and between reflecting in and out.

A very wide variety of known microscopes, such as stereomicroscopes and in particular surgical microscopes, can of course be used as microscopes. The invention is not limited to a specific microscope configuration.

- 20 In the context of a stereomicroscope, it is preferred if receptacles or recesses for carriers are provided in both beam paths. The configuration according to the present invention then makes it possible to insert different microscope accessories into the two beam paths in accordance with the particular application.

BRIEF DESCRIPTION OF THE DRAWINGS

- 25 The invention will be described below in more detail with reference to an exemplary embodiment, referring to the drawings in which:

FIGS. 1 and 2 explain the existing art and the limitations of the existing art; and

FIG. 3 shows an exemplary embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

In the Figures that follow, identical parts are always labeled with
5 the same reference characters, so that in the description of FIGS. 2 and 3,
duplicate presentation of matching parts is at least partially dispensed with.

FIG. 1 shows the basic configuration of a known microscope. In order to simplify
the depiction, both the microscope objective (or objectives) and the eyepieces are
omitted. FIG. 1 depicts only a basic body part or beam splitter housing part or
10 chassis part 1 of the microscope, in which a first beam path and a second beam
path R extend, in the direction of the arrows along the dot-dash lines, from the
microscope objectives (not depicted) or from a common objective to the eyepieces
(not depicted).

In the microscope depicted in FIG. 1, splitter prisms 2 and 3, which reflect a
15 portion of the light (L1 and R1) out of the beam path (L2 and R2) that passes
through to the eyepieces, are immovably inserted into basic body part 1. In the
exemplary embodiment depicted in FIG. 1, microscope accessories 4 and 5
(depicted only schematically) – which can be, for example, simultaneous
observation capabilities or video receivers – are mounted on basic body part 1.

20 As a result of the configuration depicted in FIG. 1, the fact that beam splitting
takes place, the direction and type of beam splitting, and the side selection (first or
second) are all unchangeably predefined, since splitter prisms 2 and 3 used as
beam splitters are immovably joined to basic body part 1.

FIG. 2 shows a variant of the microscope depicted in FIG. 1 in which, instead of
25 splitter prism 2, a splitter prism 2' that reflects in or deflects light from microscope

accessory 4' toward the first eyepiece (not depicted) is used. The reflected-in beam path L1' and beam path L are thus superimposed to yield beam path L2' in an observer's eye. The second beam path R corresponds to the beam path described in conjunction with FIG. 1. This variant also has the disadvantages described above.

- 5 FIG. 3 shows an exemplary embodiment of the invention in which, as in FIG. 2, splitter prisms 2' and 3' are arranged in the first and second beam paths L and R, respectively.

Unlike in the known microscopes described in conjunction with FIGS. 1 and 2, splitter prisms 2' and 3' are not joined to basic body part 1 but rather are
10 components of microscope accessories 4 and 5, respectively. Microscope accessories 4 and 5, which serve as carriers of splitter prisms 2' and 3, are configured in such a way that they can be inserted into a receptacle or recess 6 of basic body part 1. The tolerances between receptacles 6 and the carrier portions of accessories 4 and 5 are designed in such a way that splitter prisms 2' and 3 are
15 aligned relative to beam paths L/L'2 and R/R2, respectively, with no further actions.

Microscope accessories 4 and 5 can of course also be exchanged with one another, or a variety of accessories, for example accessories that reflect the beam path out, can be inserted into both recesses 6. Basic body part 1 can moreover also contain
20 multiple recesses or receptacles 6 in each beam path.